



Shenzhen Anywii Electronics Technology Co., Ltd

web:
www.anywiitech.com
Tel / Fax: (86) 755 8672 0744
Wechat/ Mob/whatsapp: 0086 13425161927
Email: yorkezhang@anywii.com

	Parameters	Photo
HC510-12	Camera,Image parameters	
	Image Sensor	1/2.8" CMOS sensor
	Pixels	8.5 million
	Resolution-fps	4K (3840 × 2160)-30fps
	Lens zoom	12x optical zoom
	Field of view	6.5°~70.9°
	Minimum illuminance	0.5Lux
	White balance	Auto/Indoor/Outdoor/Manual
	Backlight control	Support
	Singal Noise Reduction/Ratio	2D&3D digital/≥ 50dB
	Focus	Manual/Auto
	Focal length	3.47mm ~41.65mm
	Speaker Tracking	
	Supported, Longest tracking distance 6-7 meters	
	Interfaces	
	HD video interface	HDMI, SDI, USB3.0, LAN(POE)
	Communication protocol interface	RS232, RS485
	Power connector	HEC3800
	Encoding	H.265/H.264/MJPEG/YUY2
	USB video class protocol	UVC 1.1
	PTZ control	Support by remote
	General parameters	
	Mechanical properties	Pan:±170°;Tilt up/down:-30°~90°
		Horizontal rotate speed:1-60°/s
		Tilt up/down speed:1-60°/s
		Preset: 9 by remote, 200 by special keyboard
		Preset accuracy:0.1°
	Color	Black
	Power adapter	AC100V-AC240V to DC12V/1.5A
	Input power	12V/1A
	Operating temperature	0°C ~40°C
	Dimensions (W*H*D)	18.1*14.9*11.5cm
	Weight(net weight)	1.2kg
	Assessories	DC 12V adapter, remote(without battery), manual, USB cable
	Certificates & Area standard	
	Electrical socket and plug	American/European/British/Australian
	Certificates	CE/ROHS/FCC
anywii		
		
anywii		
		
Remark: 1. Payment term: T/T 40% as deposit, 60% TT in advance. 2. MOQ: None for neutral(100pcs for customized) 3. Port of shipmnet : FOB ShenZhen 4. Lead time: 40days after deposit and confirm everything 5. Validity: within 15 days		