



Shenzhen Anywii Electronics Technology Co., Ltd

web: www.anywii.com
www.anywiitech.com
Tel / Fax: (86) 755 8672 0744
Wechat/ Mob/whatsapp: 0086 13425161927
Email: yorkezhang@anywii.com

	Parameters		Photo
HC531-25	Camera,Image parameters		
	Image Sensor	Sony High-quality CMOS sensor	
	Pixels	8.5 million	
	Resolution-fps	4K (3840 × 2160)-60fps	
	Lens zoom	25x optical zoom	
	Field of view	59.2°	
	Minimum illuminance	0.05Lux	
	White balance	Auto/Indoor/Outdoor/Manual	
	Backlight control	Support	
	Singal Noise Reduction/Ratio	2D&3D digital/≥55dB	
	Focus	Manual/Auto	
	Focal length	6.25mm ~125mm	
	Auto Tracking		
	Supported, Longest tracking distance 6-7 meters		
	Interfaces		
	HD video interface	HDMI, SDI, USB3.0, LAN(POE)	
	Communication protocol interface	RS232, RS485	
	Power connector	HEC3800	
	Encoding	H.265/H.264/MJPEG/YUY2	
	USB video class protocol	UVC 1.1	
	PTZ control	Support by remote	
	General parameters		
	Mechanical properties	Pan:±162.5°;Tilt up/down:-30°~90°	
		Horizontal rotate speed:1-100°/s	
		Tilt up/down speed:1-70°/s	
		Preset: 9 by remote, 200 by special keyboard	
		Preset accuracy:0.1°	
	Color	Black	
	Power adapter	AC100V-AC240V to DC12V/1.5A	
	Input power	12V/2.5A	
	Operating temperature	-10℃ ~50℃	
	Dimensions (W*H*D)	22*14.4*15.9cm	
Weight(net weight)	1.7kg		
Assessories	DC 12V adapter, remote(without battery), manual, USB cable		
Certificates & Area standard			
Electrical socket and plug	American/European/British/Australian		
Certificates	CE/ROHS/FCC		
Remark: 1. Payment term: T/T 40% as deposit, 60% TT in advance. 2. MOQ: None for neutral(100pcs for customized) 3. Port of shipmnet : FOB ShenZhen 4. Lead time: 40days after deposit and confirm everything 5. Validity: within 15 days			