



	Parameters	Photo		
HC730	Camera,Image parameters			
	Image Sensor	High-quality CMOS sensor		
	Pixels	2 mega pixels		
	Highest Resolution- fps	By SDI: 1080P-60fps By HDMI: 1080P-60fps		
	Lens zoom	30x optical zoom		
	Field of view	2.34°~65.1°		
	Minimum illuminance	0.5Lux		
	White balance	Auto/Manual/3000K/3500K/4000K/4500K/5000K/5500K/6000K/6500K/7000K		
	Backlight control	Support		
	Singal Noise Reduction/Ratio	2D&3D digital/≥55dB		
	Focus	Manual/Auto		
	Focal length	4.3mm~129mm		
	Interfaces			
	HD video interface	SDI/HDMI/LAN(support RTMP、RTSP、ONVIF、GB/T28181)		
	Audio interface	3.5mm audio port		
	Communication protocol interface	8-pole mini DIN(RS232),3.81 seat (RS485)		
	Power connector	HEC3800 power socket		
	Encoding	H.265/H.264		
	USB video class protocol	UVC 1.1		
	PTZ control	Support by remote		
	General parameters			
	Mechanical properties	Pan:±170°;Tilt up/down:-30°~90°		
		Horizontal rotate speed:0.1-60°/s		
		Tilt up/down speed:0.1-30°/s		
		Preset: 10 by remote, 255 by special keyboard		
	Color	Gray		
	Power adapter	AC100V-AC240V to DC12V/1.5A		
	Input power	12V/1A		
	Operating temperature	-10°C ~50°C		
	Dimensions (W*H*D)	25.5*21.8*24.5cm		
Weight(net weight)	2.1kg(1.2kg)			
Assessories	DC 12V adapter, remote(without battery), manual, RS232 cable			
Certificates & Area standard				
Electrical socket and plug	American/European/British			
Certificates	CE/ROHS/FCC			

Remark:

1. Payment term: T/T 40% as deposit, 60% TT in advance.
2. MOQ: None for neutral(100pcs for customized)
3. Port of shipmnet : FOB ShenZhen
4. Lead time: 40days after deposit and confirm everything
5. Validity: within 15 days